




MCCB (1S, 2W)		MCCB (0.5S)	
220V	30A	220V	20A
380V	15A	380V	10A
440V	15A	440V	10A
460V	15A	460V	10A
480V	15A	480V	10A

TERMINAL BLOCK														
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
L101	L201	L301	UP01	W001	W001	REST	FA01	WE01	MS	AC	AC1	TP	TP	



NOTE

- POWER WIRE : 2.5SQ BLACK
- CONTROL WIRE : 1.5SQ RED
- EARTH WIRE : 2.5SQ GREEN

MOTOR SPEC.

- HOIST :
3φ 1.8kW 4P, 6P (1S, 2W)
3φ 0.8kW 4P, 6P (0.5S)
- TROLLEY : 3φ 0.4kW 4P, 6P

ABBREVIATION

CT : CURRENT TRANSFORMER
EMPR : ELECTRONIC MOTOR PROTECTION RELAY
DBR : DYNAMIC BRAKING RESISTOR
TP : THERMAL PROTECTOR
EM : EMERGENCY
RD : RED
BK : BLACK

TITLE		SHEET	
EDSTM-0.5S,1S,2W		1/1	
3Phase 220,380,440,460,480V 50/60Hz		REVISION NO	
CIRCUIT DIAGRAM		0	
DRAWING	CHECKED	REVIEWED	APPROVED
S.T			Y.K
17.09.19			17.09.19

DAESAN INoTEC INC.